

Packaging specifications Dimensions in mm.

SMD DEVICES

DEVICE TYPE (OUTLINE)	P	W	F	Ao	Ko	Bo	W1	W2	d	D	UNITS PER REEL	APPROX. GROSS WEIGHT
DO214AC / SMA	4 ± 0.1	12 ± 0.3	5.5 ± 0.05	2.9 ± 0.1	2.4 ± 0.1	5.4 ± 0.1	12.4 ± 0.2	16.4 ± 0.2	12.75 ^{+0.15} ₋₀	330max	7500	0.841 Kg.
	4 ± 0.1	12 ± 0.3	5.5 ± 0.05	2.9 ± 0.1	2.4 ± 0.1	5.4 ± 0.1	12.4 ± 0.2	16.4 ± 0.2	12.75 ^{+0.15} ₋₀	180max	1500	0.219 Kg.
	4 ± 0.1	12 ± 0.3	5.5 ± 0.05	2.9 ± 0.1	2.4 ± 0.1	5.4 ± 0.1	14.4max	18.4max	13 ± 0.5	330max	7500 *	1 Kg.
	4 ± 0.1	12 ± 0.3	5.5 ± 0.05	2.9 ± 0.1	2.4 ± 0.1	5.4 ± 0.1	14.4max	18.4max	13 ± 0.5	180max	1800 *	0.29 Kg.
DO214AA / SMB	8 ± 0.1	12 ± 0.3	5.5 ± 0.05	3.8 ± 0.1	2.6 ± 0.1	5.4 ± 0.1	12.4 ± 0.2	16.4 ± 0.2	12.75 ^{+0.15} ₋₀	330max	3200	0.613 Kg.
	8 ± 0.1	12 ± 0.3	5.5 ± 0.05	3.8 ± 0.1	2.6 ± 0.1	5.4 ± 0.1	12.4 ± 0.2	16.4 ± 0.2	12.75 ^{+0.15} ₋₀	180max	750	0.186 Kg.
	8 ± 0.1	12 ± 0.3	5.5 ± 0.05	3.8 ± 0.1	2.6 ± 0.1	5.4 ± 0.1	14.4max	18.4max	13 ± 0.5	330max	3000 *	0.8 Kg.
	8 ± 0.1	12 ± 0.3	5.5 ± 0.05	3.8 ± 0.1	2.6 ± 0.1	5.4 ± 0.1	14.4max	18.4max	13 ± 0.5	180max	850 *	0.24 Kg.
DO214AB / SMC	8 ± 0.1	16 ± 0.3	7.5 ± 0.05	6.4 ± 0.1	2.6 ± 0.1	8.4 ± 0.1	16.4 ± 0.2	20.4 ± 0.2	12.75 ^{+0.15} ₋₀	330max	3500	1.140 Kg.
	8 ± 0.1	16 ± 0.3	7.5 ± 0.05	6.4 ± 0.1	2.6 ± 0.1	8.4 ± 0.1	16.4 ± 0.2	20.4 ± 0.2	12.75 ^{+0.15} ₋₀	180max	850	0.306 Kg.
	8 ± 0.1	16 ± 0.3	7.5 ± 0.05	6.4 ± 0.1	2.6 ± 0.1	8.4 ± 0.1	16.4max	22.4max	13 ± 0.5	330max	3000 *	1.2 Kg.
	8 ± 0.1	16 ± 0.3	7.5 ± 0.05	6.4 ± 0.1	2.6 ± 0.1	8.4 ± 0.1	16.4max	22.4max	13 ± 0.5	180max	850 *	0.37 Kg.
DO219AA / M1F	4 ± 0.1	8.15 ± 0.1	3.5 ± 0.05	1.9 ± 0.1	1.43 ± 0.1	3.8 ± 0.1	8.5max	14.2max	13 ± 0.5	330max	7500	0.76 Kg.

* Only valid for Schottkies.

