

SMD DEVICES

DEVICE TYPE (OUTLINE)	P	W	F	Ao	Ko	Bo	W1	W2	d	D	UNITS PER REEL	PACKAGING CODE	APPROX. GROSS WEIGHT
DO214AC / SMA	4 ± 0.1	12 ± 0.3	5.5 ± 0.05	2.9 ± 0.1	2.4 ± 0.1	5.4 ± 0.1	12.4 ± 0.2	16.4 ± 0.2	12.75 <sup>+0.15</sup> <sub>-0</sub>	330max	7500	TRTB	0.841 Kg.
	4 ± 0.1	12 ± 0.3	5.5 ± 0.05	2.9 ± 0.1	2.4 ± 0.1	5.4 ± 0.1	12.4 ± 0.2	16.4 ± 0.2	12.75 <sup>+0.15</sup> <sub>-0</sub>	180max	1500	TRTS	0.219 Kg.
	4 ± 0.1	12 ± 0.3	5.5 ± 0.05	2.9 ± 0.1	2.4 ± 0.1	5.4 ± 0.1	14.4max	18.4max	13 ± 0.5	330max	7500 *	TRTB	1 Kg.
	4 ± 0.1	12 ± 0.3	5.5 ± 0.05	2.9 ± 0.1	2.4 ± 0.1	5.4 ± 0.1	14.4max	18.4max	13 ± 0.5	180max	1800 *	TRTS	0.29 Kg.
DO214AA / SMB	8 ± 0.1	12 ± 0.3	5.5 ± 0.05	3.8 ± 0.1	2.6 ± 0.1	5.4 ± 0.1	12.4 ± 0.2	16.4 ± 0.2	12.75 <sup>+0.15</sup> <sub>-0</sub>	330max	3200	TRTB	0.613 Kg.
	8 ± 0.1	12 ± 0.3	5.5 ± 0.05	3.8 ± 0.1	2.6 ± 0.1	5.4 ± 0.1	12.4 ± 0.2	16.4 ± 0.2	12.75 <sup>+0.15</sup> <sub>-0</sub>	180max	750	TRTS	0.186 Kg.
	8 ± 0.1	12 ± 0.3	5.5 ± 0.05	3.8 ± 0.1	2.6 ± 0.1	5.4 ± 0.1	14.4max	18.4max	13 ± 0.5	330max	3000 *	TRTB	0.8 Kg.
	8 ± 0.1	12 ± 0.3	5.5 ± 0.05	3.8 ± 0.1	2.6 ± 0.1	5.4 ± 0.1	14.4max	18.4max	13 ± 0.5	180max	850 *	TRTS	0.24 Kg.
DO214AB / SMC	8 ± 0.1	16 ± 0.3	7.5 ± 0.05	6.4 ± 0.1	2.6 ± 0.1	8.4 ± 0.1	16.4 ± 0.2	20.4 ± 0.2	12.75 <sup>+0.15</sup> <sub>-0</sub>	330max	3500	TRTB	1.140 Kg.
	8 ± 0.1	16 ± 0.3	7.5 ± 0.05	6.4 ± 0.1	2.6 ± 0.1	8.4 ± 0.1	16.4 ± 0.2	20.4 ± 0.2	12.75 <sup>+0.15</sup> <sub>-0</sub>	180max	850	TRTS	0.306 Kg.
	8 ± 0.1	16 ± 0.3	7.5 ± 0.05	6.4 ± 0.1	2.6 ± 0.1	8.4 ± 0.1	16.4max	22.4max	13 ± 0.5	330max	3000 *	TRTB	1.2 Kg.
	8 ± 0.1	16 ± 0.3	7.5 ± 0.05	6.4 ± 0.1	2.6 ± 0.1	8.4 ± 0.1	16.4max	22.4max	13 ± 0.5	180max	850 *	TRTS	0.37 Kg.
DO219AA / M1F	4 ± 0.1	8.15 ± 0.1	3.5 ± 0.05	1.9 ± 0.1	1.43 ± 0.1	3.8 ± 0.1	8.5max	14.2max	13 ± 0.5	330max	7500	TRTB	0.76 Kg.

\* Only valid for Schottkies.

