


SAT to IP STREAMER

IPolo series



MODEL	SIT 402	SIT 422
Reference	8240	8241
INPUT		
Inputs	4	
Standard	DVB-S2 (EN 302 307) / DVB-S (EN 300 421)	
Frequency	MHz	950 ÷ 2150
Input level	dBµV	47 ÷ 86
Baud rate	Mbps	1÷45 (DVB-S2) / 1÷62 (DVB-S)
FEC mode	LDPC+BDH (DVB-S2) / QPSK (DVB-S)	
Code rate	1/2, 2/3, 3/5, 3/4, 4/5, 5/6, 7/8, 8/9, 9/10	
Roll off	0.15, 0.20, 0.25, 0.35	
LNB control	22 KHz 13/17 V or DiSEqC 1.0	
DVB-SI AND TS PROCESSING		
Conditional Access	NO	DVB-CI: EN 50221
Table Processing	PAT, PMT, SDT, NIT, BAT, RST, PID filtering, Service creation	
Output format	SPTS/MPTS	
OUTPUT		
Number	2 independent	
Physical Standard	Ethernet 100-BaseT over RJ-45 (IEEE 802.3u)	
TCP/IP Streaming protocol	RTP/UDP/IP multicast	
Signaling protocols	SAP	
CONTROL INTERFACE		
Physical Standard	Ethernet 1000-BaseT over RJ-45	
Protocol	Web server	

Fagor Electrónica, S.Coop.

San Andrés, s/n. E-20500 Mondragón (Spain)

Tel.: +34 943 71 25 26 Fax: +34 943 71 28 93

E-mail: rf.sales@fagorelectronica.es www.fagorelectronica.com

